GM150R(P) S/W

Full IP66 True Flat PCAP/5W Touch Monitor



Feature

- ✓ Fanless design and compact solution
- ✓ Aluminum Full IP66 compliant 6-sided with hairy brush
- ✓ Resolution: 1024 x 768 dpi
- ✓ True Flat 5W/PCAP touch solution
- ✓ Waterproof connector
- ✓ 1 x VGA , 1 x USB or 1 x RS232 for Touch Screen

I/O Port	
VGA	1
USB or RS232	1
Power	
DC IN 12 V(Default) or 19~36V	
Touch Screen	**OS Support**
PCAP for 150P/5 wire resistive for 150R	Win 7.8.10; Win Embedded 7,8,10, Win pro 7,8,10
Display	
Size	15" TFT (4:3)
Resolution	1024 x 768
Colors	16.2 M
Luminance (cd/m2)	400
Contrast Ratio	700:1
View Angle (H / V)	160/160
Mechanical & Environmental	
Operation Temperature	0 ~ 45°C for 150P/RS ; -20~55°C for 150P/RW
Storage Temperature	-10°C ~ 70°C
Storage Humidity	10 ~ 90%, non-condensing
Mount	VESA mounting(100X100mm)
Dimension (W x H x D mm)&Weight	390 x 304 x 51
Optional	
HDMI	1
DVI	1
No Touch Screen	1
Optical Bonding	1

Optional High Brightness Panel					
Resolution	1024 x 768				
Color	16.2 M	16.7 M	16.7 M	16.2 M	16.7 M
Luminance(cd/m2)	2000	1600	1000	1000	800
Contrast Ratio	700:1	700:1	1700:1	700:1	700:1
Viewing Angle (H/V°)	160/160	160/160	170/170	160/160	160/160

** Specifications are subject to change without notice.