GM-170R(P) S/W

Full IP66 True Flat PCAP/5W Touch Monitor



Feature

- ✓ Fanless design and compact solution
- ✓ Aluminum Full IP66 compliant 6-sided with hairy brush
- ✓ Resolution 1280 x 1024 dpi
- ✓ True Flat 5W/ PCAP touch solution
- ✓ Waterproof connector
- ✓ 1 x VGA, 1 x USB or RS232 for Touch Screen

I/O Port	
VGA	1
USB or RS232	1
Power	
DC IN 12 V(Default) or 19~36V	
Touch Screen	**OS Support**
PCAP for 170P/5 wire resistive for 170R	Win 7.8.10; Win Embedded 7,8,10, Win pro 7,8,10
Display	
Size	17" TFT (4:3)
Resolution	1280 x 1024
Colors	16.7 M
Luminance (cd/m2)	350
Contrast Ratio	1000:1
View Angle (H / V)	140/170
Mechanical & Environmental	
Operation Temperature	0 ~ 45°C for 170P/RS or -20 ~ 55°C for 170P/RW
Storage Temperature	-10°C ~ 70°C
Storage Humidity	10 ~ 90%, non-condensing
Mount	VESA mounting(100 X 100 mm)
Dimension (W x H x D mm)&Weight	TBD
Optional	
DVI	1
HDMI	1
No Touch Screen	1
Optical Bonding	1

Optional High Brightness Panel			
Resolution	1280 x 1024		
Color	16.7 M	16.7 M	16.7 M
Luminance(cd/m2)	1600	1000	800
Contrast Ratio	1000:1	1000:1	1000:1
Viewing Angle (H/V°)	170/170	160/160	160/160

*Specifications are subject to change without notice.

Inspiring a Reliable Solution

www.kingdy.com.tw