GM-190R(P) S/W

Full IP66 True Flat PCAP/5W Touch Monitor



Feature

- ✓ Fanless design and compact solution
- ✓ Aluminum Full IP66 compliant 6-sided with hairy brush
- ✓ Resolution 1280 x 1024 dpi
- ✓ True Flat 5W/PCAP touch solution
- ✓ Waterproof connector
- ✓ 1 x VGA, 1 x USB or RS232

I/O Port	
VGA	1
USB or RS232	1
Power	
DC IN 12 V(Default) or 19~36V	
Touch Screen	**OS Support**
PCAP for 190P/5 wire resistive for 190R	Win 7.8.10; Win Embedded 7,8,10, Win pro 7,8,10
Display	
Size	19" TFT (4:3)
Resolution	1280 x 1024
Colors	16.7 M
Luminance (cd/m2)	250
Contrast Ratio	1000:1
View Angle (H / V)	170/160
Mechanical & Environmental	
Operation Temperature	0 ~ 45°C for 190P/RS or -20 ~ 55°C for 190P/RW
Storage Temperature	-10°C ~ 70°C
Storage Humidity	10 ~ 90%, non-condensing
Mount	VESA mounting(100 X 100 mm)
Dimension (W x H x D mm)&Weight	521.4 x 434.4 x 67.1 (11kg)
Optional	
HDMI	1
DVI	1
No Touch Screen	1
Optical Bonding	1

Optional High Brightness Panel				
Resolution	1280 x 1024			
Color	16.7 M			
Luminance(cd/m2)	1600	1000	1000	800
Contrast Ratio	1000:1	2000:1	1000:1	1000:1
Viewing Angle (H/V°)	170/160	178/178	160/170	170/160

*Specifications are subject to change without notice.

Inspiring a Reliable Solution

www.kingdy.com.tw